Logo Placements
1132 HV Jacket Class 3

Recommended logo placements
Heat seal

1	Left breast, 1 cm above pocket, maximum size 60x60 mm or 100x20 mm
2	Left sleeve, 5 cm below shoulder seam, maximum size 120x120 mm
3	Right breast, maximum size 60x60 mm or 100x20 mm
4	Right sleeve, 5 cm below shoulder seam, maximum size 120x120 mm
6	Back, 2 cm below yoke seam, maximum size 180x280 mm, logo might not be visible when the hood is down
23	Right breast, top of logo lining with placement, maximum size 120x120 mm
24	Left breast, top of logo in line with top of zipper, maximum size 60x80 mm
62	Back, 13 cm below yoke seam maximum size 250x280 mm

Add
B after the placement and it will be below the (1B)
Y and it will be turned from bottom to top
Z after the placement and it will be turned from top to bottom



Maximum size of logo cm^2 to keep classification EN20471

Size	cm^2	cm
XS	484	22x22
S	1290	35x35
M-4XL	2130	46x46

How to keep classification ISO EN 11612

Labels, badges, retro-reflective materials, transfers, etc., which are applied to the outermost surface of the garment, with an area > 10 cm^2 shall be tested in ISO 15025, Procedure A.

e-snickers uniwork

www.e-snickers.nl